Security in SDN/NFV and 5G Networks – Opportunities and Challenges

Ashutosh Dutta, Ph.D.
Senior Scientist, Johns Hopkins University Applied Physics Lab (JHU/APL), USA
Co-Chair, IEEE Future Network Initiative
IEEE Communications Society Industry Outreach
IEEE Communications Society Distinguished Lecturer
Email: ashutosh.dutta@ieee.org; Ashutosh.Dutta@jhuapl.edu
05/06/2019

Talk Outline

- Drivers for SDN/NFV and 5G Networks
- Cellular Technology Evolution
- Key 5G Characteristics
- Threat Taxonomy
- Opportunities and Challenges in Security Virtualization and 5G
- Security Use Cases
- Industry Standards Activities and Testbed
- Summary

Emerging Services and Applications

A Driver for Network Evolution

IEEE

SLAs associated with Types of Applications



Source Nokia

Evolution of wireless access technologies



5G

10 Gbps DL Speed

IEEE

Co-existence of IEEE and 3GPP Technologies



Key Characteristics of 5G

- Massive MIMO
- RAN Transmission – Centimeter and Millimeter Waves
- New Waveforms
- Shared Spectrum Access
- Advanced Inter-Node Coordination
- Simultaneous Transmission Reception
- Multi-RAT Integration & Management
- D2D Communications
- Efficient Small Data Transmission
- Densification of Small Cells
- Wireless Backhaul / Access Integration
- Flexible Networks
- Flexible Mobility
- Context Aware Networking
- Information Centric Networking
- Moving Networks

5G – Emerging Architecture and Enabling Technologies

5G Architecture Themes: Flexibility, Scalability



Source: 5G-PPP Architecture WG View on 5G Architecture (Version 2.0)

5G New Radio

–Fiber-like performance

–However, 5G is Multi-RAT

- Network Function Virtualization
  - Network realized in software: Core and RAN
  - Cloud resources throughout the network
- Programmable Network
  - Flexible orchestration of network resources and infrastructure: RAN, core, transport, etc.
- Network Slicing
  - Self-contained, independent network partition including all segments: radio, core, transport, and edge.
  - Multi-domain, multi-tenant

IEEE

5G Dimensions and Types of 5G Applications

Enhanced Mobile Broadband

- Mobile Broadband, UHD / Hologram, High-mobility, Virtual Presence, Virtual Reality

Critical Communications

- Interactive Game / Sports, Industrial Control, Drone / Robot / Vehicle, Emergency, Self-driving vehicles

Massive Machine Type Communications

- Subway / Stadium Service, eHealth, Wearables, Inventory Control

Network Operation

- Network Slicing, Routing, Migration and Interworking, Energy Saving

Enhancement of Vehicle-to-Everything

- Autonomous Driving, safety and non-safety features



Courtesy: Gerhard Fettweis

IEEE

Enhanced Mobile Broadband & UHRLLC Use Cases

- Enhanced Mobile Broadband (eMBB)
  - Expected throughput of 5 Gbps +
  - UHD video (4k, 8k), 3D video (including broadcast services)
  - Virtual Reality
  - Augmented Reality
  - Tactile Internet
  - Cloud gaming
  - Broadband kiosks
  - Vehicular (cars, buses, trains, aerial stations, etc.)

- High reliability / low latency
  - Industrial control
  - Remote manipulation
  - Mission-critical applications e.g. ehealth, hazardous environments, rescue missions, etc.
  - Self-driving vehicles



Source: ITU-R

What “5G and Advanced Communication Systems” is About

SDN/NFV is the Foundation of 5G Core Network



Traditional Network vs. SDN/NFV Network



Virtualized Networks

- General purpose cloud-based hardware components
- Software-based virtual network components and services
- Dynamic real-time configuration to support internal or customer activity
- Programmable network management
  - Software Defined Network controls
  - Real-time analytics and policy driven orchestration of service, network and capacity requests

Traditional Networks

- Built using purpose-built hardware coupled with physical connectivity
- Control logic largely coordinated and implemented by layers of OSSs
- Control, Forward and Data Planes are tightly integrated in Network Elements
  - OA&M, inventory views and operational controls managed in OSSs to avoid negative impact to service performance

Overview of NFV (Network Function Virtualization) Sample Use cases



NFV Use Case: Dynamic VNF Placement of Mobile Core Network (EPC) and IMS Elements

Network Operation





VNF Relocation

An Example - Security Transformation – Virtual Firewall/Virtual DDOS/Virtual IPS

Non-Virtualized Security

- Wide variety of vendor specific security hardware
- Requires vendor specific FW management platforms
- Requires hands-on customized physical work to install
- Multiple support organizations
- No single operations model or database of record

Virtualized Security Function



- Security functions will be cloud-based
- Security dynamically orchestrated in the cloud as needed
- Streamlined supplier integration
- Centralized common management platform
- Creates a standard operations/support model

IEEE

Security Challenges in SDN/NFV Environment ETSI Problem Statement Draft

- Hypervisor Vulnerability
- API security
- Orchestration Vulnerability
- Virtual monitoring
  - Limited visibility to Mobility/EPC interfaces (e.g. S6a, S11, S8)
- Virtualized firewalls
- Secure boot
- Secure crash
- User/tenant authentication, authentication and accounting
- Topology validation and enforcement
- Performance isolation
- Authenticated Time Service
- Private Keys within Cloud Images
- Detection of attacks on resources in virtualization infrastructure
- Security monitoring across multiple administrative domains (i.e., Lawful Interception)



IEEE

Key Pillars of SDN/NFV and 5G Security



Open Source Security

Network Slicing Security

Edge Security

Security Function Virtualization (Security-as-a-Service

Cloud RAN Security

SDN Controller Security

Faster Authentication

Proactive Security Analytics

Orchestration Security

Hypervisor Security

May 7, 2019

General Threat Taxonomy (EPC) – Ref. ETSI/NFV Monitoring and Management (Draft 13)

LTE/EPC Security Threats Categories



Mobile Network Security - EPC
Threat Categories

	Category	Threat	Description
T1	Loss of Availability	Flooding an interface	Attackers flood an interface resulting in DoS condition (e.g. multiple authentication failure on s6a, DNS lookup)
T2		Crashing a network element	Attackers crash a network element by sending malformed packets
T3	Loss of Confidentiality	Eavesdropping	Attackers eavesdrop on sensitive data on control and bearer plane
T4		Data leakage	Unauthorized access to sensitive data on the server (HSS profile, etc.)
T5	Loss of Integrity	Traffic modification	Attackers modify information during transit (DNS redirection, etc.)
T6		Data modification	Attackers modify data on network element (change the NE configurations)
T7	Loss of Control	Control the network	Attackers control the network via protocol or implementation flaw
T8		Compromise of network element	Attackers compromise of network element via management interface
T9	Malicious Insider	Insider attacks	Insiders make data modification on network elements, make unauthorized changes to NE configuration, etc.
T10	Theft of Service	Service free of charge	Attackers exploits a flaw to use services without being charged

Attacks Taxonomy – VoLTE/IMS/USP



IMS Threat Categories

	Category	Threat	Description
T1	Loss of Availability	Flooding an interface	DDoS/TDoS via Mobile end-points
T2		Crashing a network element	DoS/TDoS via rogue media streams and malformed packets
T3	Loss of Confidentiality	Eavesdropping	Eavesdropping via sniffing the SGi(Gm) interface
T4		Data leakage	Unauthorized access to sensitive data on the IMS-HSS
T5	Loss of Integrity	Traffic modification	Man-in-the-middle attack on SGi(Gm) interface
T6		Data modification	SIP messaging impersonation via spoofed SIP messages
T7	Loss of Control	Control the network	SPIT(Spam over Internet Telephony) / unsolicited voice calls resulting in Voice-SPAM/TDoS
T8		Compromise of network element	Compromise of network element via attacks from external IP networks
T9	Malicious Insider	Insider attacks	Malicious Insider makes unauthorized changes to IMS-HSS, SBC, P/I/S-CSCF configurations
T10	Theft of Service	Service free of charge	Theft of Service via SIP messaging impersonation

Attacks on LTE-RAN



RAN Threat Categories

	Category	Threat	Description
T1	Loss of Availability	Flooding an interface	DOS on eNodeB via RF Jamming
T2		Crashing a network element	DDOS on eNodeB via UE Botnets
T3	Loss of Confidentiality	Eavesdropping	Eavesdropping on S1-MME/S1-U interfaces
T4		Data leakage	Unauthorized access to sensitive data on the eNodeB
T5	Loss of Integrity	Traffic modification	Man-in-the-Middle attack on UE via false eNodeB
T6		Data modification	Malicious modification of eNodeB configuration data
T7	Loss of Control	Control the network	Attackers control the eNodeB via protocol or implementation flaw
T8		Compromise of network element	Attackers compromise the eNodeB via management interface
T9	Malicious Insider	Insider attacks	Malicious Insider makes unauthorized changes to eNodeB configuration
T10	Theft of Service	Service free of charge	Theft of Service via Spoofing/Cloning a UE

SDN/NFV-based Evolved Packet Core



Security Advantages of SDN/NFV

A Comprehensive View of SDN/NFV Security Advantages

Performance Improvements:

Streamline and Reduce Incident Response Cycle Time

Streamline and Reduce Patching Cycle Time

Design Enhancements:

Centralize Control and Management Functions

Security Embedded at Design Time

Security that Exceeds Existing Perimeter

Multivendor Security Service



Real-Time capabilities:

Real-Time Scaling to Absorb DDOS Attacks

Real-Time Integration of "Add-on" Security Functions

IEEE

Security Opportunities from Virtualization

DDoS Attack Resiliency – Control Plane



Security Opportunities from Virtualization

SDN Controller Dynamic Security Control – Data Plane



Security Challenges from Virtualization

Hypervisor Vulnerabilities

To prevent this type of attack, we must:

- ✓ Conduct security scans and apply security patches
- ✓ Ensure the Hypervisor is hardened and minimized (close vulnerable ports)
- ✓ Ensure the access to the Hypervisor is controlled via User Access Management,

3



Malware compromises VMs:

- VM/Guest OS manipulation
- Data exfiltration/destruction

2

Hacker exploits a vulnerability in the Open Source code and infects the Hypervisor with a Malware

1

IEEE

Security Vulnerability in ODL SDN Controller



- Denial of Service Attack through South Bound Interface
- REST API Parameter Exploitation – North Bound API
- North Bound API Flood Attack
- MAN-IN-THE MIDDLE ATTACK/Spoofing
- Protocol Fuzzing – South Bound
- Controller Impersonation – South Bound

DNS Amplification Attacks Enhanced by Elasticity Function



Network Function Virtualization

Security Challenges and Opportunities

Existing Threats

New Virtualization Threats

Security Opportunities

DDoS Mitigation Scheme

Security Function Virtualization

Exploit Orchestration Vulnerability

DDoS/ Attacks from the Internet

DDoS Signaling Storm by Mobile Devices

Orchestration

vMME | vHSS | vPCRF

vS-GW | vP-GW | vPCEF

Hypervisor

Common Hardware

SDN

vEPC

S1-MME

S1-U

SGi



Real Time Services

Internet

Cloud Services

Partner Networks

Attacks from User Plane by Mobile Devices

Exploit Hypervisor Vulnerability

Amplification Attacks Enhanced by Elasticity Function

IEEE

Threat Scenarios in NFV - Enterprise Networks(Reference - ETSI NFV)



Security Pillars for 5G Core

RAN
(Cloud RAN / vRAN)



Network Slicing

Mobile Edge

Security Use Cases for 5G RAN

DDOS attacks against Network Infrastructure

- Overload of the signaling plane by a huge number of infected M2M/IOT devices that attempt to gain access
- Overload of the signaling plane by a huge number of infected M2M/IOT devices that transmit intermittently and simultaneously
- Resource Starvation at cRAN vFW
- Leverage IOT for Distributed Denial of Service
- Resource Sharing by multiple service providers at cRAN
- Deliberate triggering of network and overload mechanisms
- Bulk configuration

Virtualization (NFV and SDN) is the Foundation upon which 5G will be Built

Opportunities and Risks associated with Virtualization will apply to 5G VNFs

Use Case: CRAN (Cloud RAN) Resource Starvation due to 5G RAN Firewall Functions

1 5G will facilitate billions of mobile devices accessing the RAN due to increased mobile video sessions, M2M, IoT and RAN-WiFi interoperability

2 A significant increase in malicious traffic from millions of IoT devices to 5G RAN

mmW, etc.
Non-3GPP (WiFi)

5G Cell Sites (RRH)

CRAN VNFs (BBU, other eNodeB functions)

CRAN VNF vFW

Hypervisor

Common HW

5G RAN (Cloud RAN)

3 vFirewall VNF in the Cloud RAN to detect and mitigate malicious traffic (Mobile Edge protection)

5G Backhaul

5G Core

4 A significant increase in malicious traffic causes the vFW to demand more compute resources, as a result, starving the other Cloud RAN VNFs

5 **Recommended Solution:**
1. Hypervisor Separation
2. Intelligent VM resource allocations

5G will Increase the Possibilities for Multiple Providers to Collaborate on a System

Increase the Risk of Compromise Shared Resources

Use Case: Compromise Shared Resources



Security Use Cases for Mobile Edge Computing

- Storage of Sensitive Security Assets at the Edge
- Third party applications on the same platform as network functions
- User Plane attacks in Mobile Edge Computing Environment
- Exchange of Sensitive Security Assets between core and Mobile Edge
- Trust establishment between functions at the core and at the edge
- Subscriber authentication within the visited network
- Secure storage of credentials to access IMS network
- Access to 5G core over non-3GPP network access
- User plane data security over less trusted 3GPP network accesses
- Management of credentials to access non-3GPP network access

Mobile Edge Computing – Use Case
Storage of Sensitive Security Context at the Mobile Edge

- IOT type applications require low latency, faster authentication and hence, need security context to be stored at the edge of the network

- Sensitive Security Assets stored at the mobile edge should be encrypted
- threat to sensitive assets while temporarily decrypted also needs to be addres

- Sensitive security assets are compromised at virtualized functions at the edge
- An attacker could maliciously reuse them to gain connectivity or carry out a spoofing, eavesdropping or data manipulation attack.

Recommended Solutions:
1. Virtual Firewalls at MEC
2. Encryption at the Edges
3. IDS/IPS to detect and mitigate spoofing and eavesdropping

MEC Server
Edge Cloud

MEC Server
Edge Cloud
VNF

MEC Server
Edge Cloud

VNF

Network Slice 1
Control Plane
vMME
vHSS
vS/PGW-C

Network Slice 2
vEPC Data Plane
vSGW-U
vPGW-U
vDNS

Network Slice 4
vIMS
vP-CSCF
vS-CSSCF
vHSS

5G Core

Internet

Mobile Edge Computing – Low Latency during Handover
Subscriber authentication within the visited network

- Consistently low latency application may require very fast authentication procedures at attachment or during handover.
- This may force subscriber authentication to be done entirely within the visited network

- Combine low latency on the user plane with high latency on the signaling plane.
- Delegated Subscriber Servers (DSSes) will help improve the latency for the signaling plane

Edge Cloud (Visited Network)

Security Cache Server

DSS

UE Handover

Network Slice 1

Control Plane

vMME

vHSS

vS/PGW-C

Network Slice 4

vIMS

vP-CSCF

vS-CSSCF

vHSS

5G Core

Recommended Solutions:

1. Encryption at the Edges
2. IDS/IPS to detect and mitigate spoofing and eavesdropping
3. Timely expiration of temporary SAs

Internet

DSS

Visited Network Edge Cloud

Security Cache Server

VNF

UE Handover

- Persistent caching of old SAs by both the UE and visited network weaken security
- There is risk of an old key leaking and being abused

VNF

Network Slice 2

Data Plane

vSGW-U

vPGW-U

vDNS

Network Slice 3

vEPC

- User plane latency can be minimized by re-using an old security association (SA), while in the meantime running AKA and acquiring a new security association.

Visited Network Edge Cloud

Security Cache Server

DSS

1 2 3 4 5

Network Slicing Use Case

Side channel attacks across Network slices

- Each slice is dedicated for a specific operator.
- These slices run on the same hardware controlled by the hypervisor

6

- If an attacker can observe or influence how code runs in functions in slice A, she/he may be able to affect the running of code in functions in the slice B machine, or extract information about the running of code in slice B.

7

- This may allow side channel attacks – in particular, timing attacks – that extract information about cryptographic keys or other secrets in slice B.

8

Slice A Slice B Slice C

PLMN # 1

PLMN # 2

1

Multi PLMN support on 5G devices

PLMN # 3

1

5G Cell Sites (RRH)

PLMN # 1 PLMN # 2 PLMN # 3

PLMN # 1 PLMN # 2 PLMN # 3

vMME vHSS vSGW vPGW vDNS Etc.

vMM vHS vSG vPG vDNS Etc.

vDNS Etc.

Hypervisor

Common HW

Internet

- Avoid co-hosting on the same hardware slices that have very different levels of sensitivity, or very different levels of vulnerability to influence by an attacker

9

5G Air Interface (mmW)

5G air interface to support multi PLMN Devices.

2

5G RAN (Cloud RAN)

5G RAN to support isolation of radio traffic based on PLMN Id.

3

5G Backhaul

Cell Site Backhaul to support IP traffic separation based on PLMN Id.

4

5G Core (AIC)

- Deploy proper isolation mechanism so that: observing or influencing how code runs in one virtual machine should not allow an attacker to influence or deduce anything about how code runs in another virtual machine on the same hardware.

9

5

1. All required core network elements (VNFs) are configured for each slice; i.e. PLMN id via VNFs in AIC.
2. CBB (MPLS) network to support separation of core network IP traffic based on PLMN Id for each slide.

Public Land Mobile Network Identity (PLMN-ID) = three digit mobile country code (MCC) + a two or three digit mobile network code (MNC

Security Use Cases for Network Slicing

- Controlling Inter-Network Communications
- Instantiation time Impersonation attacks against Network Slice Manager
- Impersonation attacks against a Network Slice instance within an Operator Network
- Impersonation attacks against different Network Slice managers within an Operator Network
- Different Security Protocols or Policies in different slices
- Denial of Service to other slices
- Exhaustion of security resources in other slices
- Side Channel Attacks Across Slices
- Hybrid Deployment Model
- Sealing between slices when UE is attached to several slices

Relevant SDN/NFV/5G Standards

Forum	Focus
IETF	Network Virtualization Overlay, Dynamic Service Chaining, Network Service Header
3GPP	Mobility and Security Architecture and Specification
ETSI ISG NFV	NFV Platform/Deployment Standards – Security, Architecture/Interfaces, Reliability, Evolution, Performance
IEEE	Develop Technologies for that can be used by other Standards Bodies. There are 42 societies to contribute to 5G Eco System
ONF	OpenFlow SDN Controller Standards
OPNFV	NFV Open Platform/eCOMP/OPNFV Community TestLabs
Openstack	Cloud Orchestrator Open Source
OpenDaylight	Brownfield SDN Controller Open Source
ONOS	OpenFlow SDN Controller Open Source
DPDK/ODP	CPU/NIC HW API – Data Plane Development Kit
KVM Forum	Hypervisor
OVS	Open Source vSwitch
Linux	Operating System, Container Security
ATIS/NIST/FCC/CSA	Regulatory Aspects of SDN/NFV

IEEE

ETSI/NFV Security Expert Group work Items

Work Items	Scope
NFV Security Problem Statement Document	Identifies and proposes solutions to any new vulnerabilities that result from the introduction of NFV
Security and Trust Guidance	Describes the security and trust guidance that is unique to NFV development, architecture and operation
Cataloguing Security Features in Management Software	Catalogue security features in management software relevant to NFV - OpenStack as the first case study.
Lawful Interception Implications	Identify the security and architecture pre-conditions for the provision of LI in an NVF based network
Certificate Management	Looks at various certificate deployment scenarios and describe certificate specific use cases
Report on Security Aspects and Regulatory Concerns	Addresses the security aspects and regulatory concerns of NFV related documents and applications
Report on Attestation Technologies and Practices for Secure Deployments	Identifies gaps in existing attestation technologies and practice
Security Monitoring – Report on Use Cases and Requirements	Investigate the security monitoring requirements and deployment use cases in an NFV environment
Use cases for multi-layer host administration	Addresses provision of multi-layer administration issues within a single host.

44

Virtual IDS Prototype for Mobility CORE

1. ***Malicious URL Detection and Mitigation***
2. ***Malware Detection and Mitigation***
3. ***Application and Overload Control***



Blacklist Detection for DSC



Malware Download Detection for GDSC




NIKSUN
135.91.153.58/ngen/main.jsp
NetDetector/NetVCR/NetMobility/Virtual Controller
Welcome admin niksun.cso.att.com 18:08:26 11/10/2014 EST
Logout
Analysis
Reports
Event Viewer
Application Reconstruction
Tools
Configuration
Virtual Controller
Help
Main Analysis
S6A Summary
EPC Load
EPC Latency
IMSI Activity
Mobility Analysis
CDMA Summary
IMS Analysis
IMS Performance
IMS Security
Drill To
Export
Start
-15 min
Stop
now
Filter
Do DNS?
Top N
20
Window
0
Update
Reset
Save
Application / Protocol Detail
Top IMSI
Top eNodeB
Top SGW
Top MME
IMSI
Sessions
Packets
Bytes
What's Busy?
diameter
diametersctp
https(443)
3868
36412
1024
gtpC
TURN
ssdp
16881
Bit Rate
Before Throttling
After Throttling
Bit Rate (bps)
Time (data points 10.0 seconds)
Who's Talking?
Host Pair

Summary

- Emerging services are evolving rapidly
- Network needs to be designed to be adaptable, resilient, and flexible
- Operators need to reduce Capex and Opex
- SDN/NFV is an enabler for 5G
- Opportunities and Challenges in this new virtualized environment
- 5G-specific application adds new security requirements
- Comprehensive security architecture is essential to take care of security challenges
- Operators and vendors need to work together to form a security ecosystem
- Standards, Testbeds and POCs act as catalyst for Virtualization

IEEE Membership By Region

Total Membership

421,355

- R1 to 6 — **194,167**
- R7 — **17,163**
- R8 — **77,883**
- R9 — **18,569**
- R10 — **113,573**
- IEEE Offices



2018 FDC Initiatives & Activities

Small Projects

- Environmental Engineering
- Roadmaps Strategy and Governance (IRSG)
- Quantum Computing

IEEE BLOCKCHAIN™

IEEE Future NETWORKS™

IEEE brain

IEEE rebooting COMPUTING

IEEE Digital Reality

IEEE SYMBIOTIC AUTONOMOUS SYSTEMS™

IEEE TECHNOLOGY TIME MACHINE

ieee.org/futuredirections

Graduated Initiatives

IEEE BigData

IEEE Smart Cities

IEEE CLOUD COMPUTING

IEEE SMARTGRID

IEEE CYBER SECURITY

IEEE SOFTWARE DEFINED NETWORKS

IEEE Internet of Things

IEEE lifesciences

IEEE TRANSPORTATION ELECTRIFICATION COMMUNITY

IEEE SUSTAINABLEICT™

Key Stakeholders

IEEE Societies (22 so far)

Industry

Academia, Students

IEEE OUs

IEEE STANDARDS ASSOCIATION

IEEE EDUCATIONAL ACTIVITIES

Initiative Profile

- Launched August 2016
- Technical Activities Board Funded
- 20+ Participating Societies/OUs

Futurenetworks.IEEE.org

Search IEEE Future Networks | Search | Join the IEEE Future Networks Community

Home | About | What's New | Conferences | Education | Publications | Standards | Tech Focus | Roadmap | 5G Summit | Podcasts | Testbeds

6G Wireless Summit
Paving the Road for the Coming of 6G
IEEE Future Networks Tutorials
IEEE 5G Summit
6G Wireless Summit
www.6gsummit.com

6G WIRELESS SUMMIT
Levi • Lapland • Finland
24-26 March 2019

What's New

Call for Papers/ Tutorials/ Proposals:
IEEE 5G World Forum
Call for Papers, Vertical/Topical Areas and more
Learn more.

IEEE Future Networks Upcoming Webinar:
Security in SDN/NFV and 5G Networks - Opportunities and Challenges
Dr. Ashutosh Dutta, Johns Hopkins University Applied Physics Labs (JHU/APL)
Learn more.

IEEE Future Networks Webinar Series on Demand:
Mitigating Thermal & Power Limitations to Enable 5G
Dr. Earl McCune, CTO, Eridan Communications
View Webinar

IEEE Workshop on 5G Technologies for Tactical and First Responder Networks
View recordings and presentations of the workshop held 23 October 2018
Learn more.

Feature Article

MWC Barcelona 2019: Low Latency 5G Networks Could be a Game-Changer for AR and VR (But Not Until 2020)

New 5G service could enable multi-player VR games and maybe even eliminate nausea

Read more at IEEE Spectrum.

Wireless Predictions 2019

Read more at ECN.

Technology Spotlight

MWC Barcelona 2019: On the Road to Self-Driving Cars, 5G Will Make Us Better Drivers

Long before we have autonomous vehicles, 5G-enabled services could keep us more alert and informed

Read more at IEEE Spectrum.

Are you Ready to Look at 6G?

Read more at Telecoms.com.

Useful Links

- Join the Team - Call for Volunteers
- Distinguished Lecturer Program
- IEEE Future Directions Newsletter
- IEEE ComSoc Technology Blog
- IEEE 5G Summit
- IEEE Future Directions Talks Future Networks: Read Q&A Interviews with IEEE experts
- IEEE Future Directions Blog

IEEE 5G and Beyond
STANDARDS DATABASE

Get Involved
IEEE FUTURE DIRECTIONS
Join Our Initiatives

Led by a steering committee of 30 leaders from a diverse set of Future Networks-related IEEE Societies

The global team of experts involved in IEEE Future Networks are producing programs and activities including…

The Future Networks Roadmap

short-term (~3 years), mid-term (~5 years), and long-term (~10 years) research, innovation, and technology trends

Standards

Global, open, and collaborative

Conferences & Events

IEEE 5G Summits

IEEE 5G World Forums

Future Networks-related IEEE conferences

Education

IEEE Future Networks Learning Series

IEEE Live Online Courses, Webinar series

Videos from IEEE 5G Summits

Expert Articles

Published on IEEE Future Networks web portal and in industry media

Publications

IEEE Future Networks Transmissions podcast series

IEEE Future Networks Tech Focus Newsletter

IEEE Future Directions Talks Future Networks Q&A article series

IEEE Future Networks Initiative Organization Structure



Roadmap Structure – Leadership and Working Group Co-chairs

Standardization Building Blocks
Paul Nikolich
Alex Gelman
Purva Rajkotia
Mehmet Ulema
mmWave and Signal Processing
Timothy Lee
Harish Krishnaswamy
Earl McCune
Hardware
Dylan Williams

Massive MIMO
Rose Quingyang Hu
Dongming Wang
Chris Ng
Chi Ming Chen
Haijian Sun
Applications and Services
Ravi Annaswamy
Narendra Mangra
Testbed
Ivan Seskar
Tracy Van Brakle

Security
Ashutosh Dutta
Ana Nieto
Ahmad Cheema
Satellite
Sastri Kota
Prashant Pillai
Giovanni Giambene
Edge Automation Platform
Meryem Simsek
Cagatay Buyukkoc
Kaniz Mahdi
Paul Littlewood

NEW FOR 2019
Systems Optimization
Ashutosh Dutta
Kaniz Mahdi
Optics
Feras Abou-Galala
Paul Littlewood
Deployment
David Witkowski

Connecting the Unconnected
Sudhir Dixit, Ashutosh Dutta

Ecosystem Stakeholders

- End users
- Application developers
- Service providers
- Equipment manufacturers
- Component suppliers
- Technology innovators
- Governments
- Standards and guidelines producing bodies

IEEE-SA

3GPP

ITU

Industry Interaction at Large

- The Roadmap effort will also include a series of meetings to gather additional inputs and feedback on trends related to:
- Business
- Technology
- Societal
- New fields
- Other industries

IEEE 5G World Forum 2019 and 2020

5G World Forum 2019 – Dresden, Germany

5G World Forum 2020, India

Connecting the Industry, Academic, Entrepreneurs and Government Around the World

GLOBAL

IS

WHAT IS NEEDED

LOCALLY EVERYWHERE

More than 50 Summits
IEEE 5G Summit Series – 2015 - 2019 (www.5gsummit.org)

50+ 5G Summits, More than 7500 attendees (onsite and online),
600 Speakers, Streaming and Recording Archived

Number of Summits
2015 – 3
2016 – 8
2017 – 19
2018 – 14
2019– 12+ (Planning underway)
Soliciting other chapters

5G Summits at a Glance 5gsummit.org



3 IEEE 5G Summits in 2015

8 IEEE 5G Summits in 2016

19 IEEE 5G Summits in 2017

14 IEEE 5G Summits in 2018

12 IEEE 5G Summits Planned in 2019

IEEE
Advancing Technology for Humanity

Whether you are a platform provider, operator, manufacturer, or service/ content provider, there is a path for you and your business to be seen, heard, and make an impact in 5G and Beyond

…contribute to the IEEE Future Network Initiative Roadmap Working Groups …

…contribute to our publication, IEEE 5G Tech Focus…

…lead an IEEE 5G use case or infrastructure project.

THANK YOU

and

JOIN US FOR THE INNOVATION REVOLUTION

LEARN MORE AT
5G.IEEE.ORG

Backup Slides

Attack Types in NFV (Ref- ETSI/NFV)

Threat 1: Attack from VMs in the same domain

- VM would be manipulated by attackers and potentially extend the attack to other VMs
- Buffer overflow, DOS, ARP, Hypervisor, vswitch

Threat 2: Attack to host, hypervisor and VMs from applications in host machine

- Poor design of hypervisors, improper configuration
- Attackers inject malicious software to virtual memory and control VM
- Malformed packet attacks to hypervisors

Threat 3: Attack from host applications communicating with VMs

- Host applications being attacked can initiate monitoring, tampering or DOS attack to communications going through host vSwitch
- Improper network isolation, Improper configuration to application privileges of host machine
- Lack of restriction to services or application

Attack Types in NFV (Ref-ETSI/NFV)(Contd.)

Threat 4: Attack to VMs from remote management path

- Outside attackers could initiate communication by eavesdropping, tampering, DOS attack, and Man-in-the-Middle attack
- Gain illegal access of the system and access OS without authorization, tamper and obtain sensitive and important information of a system
- Poor design and development of the application may lead to many known attacks (e.g., buffer overflow attacks)

Threat 5: Attack to external communication with 3rd party applications

- The API interface accessed by 3rd party applications in the untrusted domains is easily subject to malicious attack. Such attack includes illegal access to API, DOS attack to API platform
- Logical bugs in APIs, API authentication/authorization mechanism problems and security policy configuration problems.

Threat 6: Attack from external network via network edge node

- Virtualized Firewalls, Residential gateways

Threat 7: Attack from host machines or VMs of external network domain

- VNF migration, VNF scaling (Scale in- Scale out)

Hypervisor Vulnerability (Example)

Use Case: Hypervisor gets compromised somehow by the attacker. Attacker uses hypervisor privilege to install kernel root kit in VNF's OS and thereby controls and modifies the VNF.

Mitigation Techniques:

- Hypervisor Introspection schemes can use the Hypervisor's higher privilege to secure the guest VMs.
- A Hypervisor-based introspection scheme can detect guest OS rootkit that got installed by the attacker.
- Adoption of Hypervisor hardening mechanisms can protect hypervisor's code and data from unauthorized modification and can guard against bugs and misconfigurations in the hardened hypervisors.
- Use Software vulnerability management procedure to make sure the hypervisor is secured from attack

Orchestration Vulnerability (Example)

Use Case: An attacker uses legitimate access to the orchestrator and manipulates its configuration in order to run a modified VNF or alter the behavior of the VNF through changing its configuration through the orchestrator. This will compromise the VNF separation as the administrator of one VNF can get admin privilege of another VNF and the separation between the VNFs cannot be maintained.

Mitigation Techniques:

- Deploy some of the inherent best current practices for orchestration security by way of detection mechanism when the separation is violated, provide secure logging for access, automated system or configuration auditing.
- Deploy security monitoring system that will detect the compromised VNF separation, any kind of anomaly in the system or provide alert mechanism when some critical configuration data in the orchestrator is altered.
- Access Control, File system protection, system integrity protection
- Hardening of separation policy through proper configuration management